



DOUBLE DISC 1300 1600

Spreaders

Discover why JF's Double Disc 1300/1600 and JF Double Disc 1300/1600 FR spreaders are perfect solutions for covering your land with productivity.

FEATURES

- ✓ Working width from 16 to 36m;
- ✓ Discs with 4 paddles with adjustable positions for uniform distribution;
- ✓ Discs, paddles, gates, and bottom closure made of stainless steel for greater strength and durability;
- ✓ Simple adjustment dosing for greater agility in operation;
- ✓ Tank made of high-resistance UV-protected polyethylene;
- ✓ Special agitator (optional) for working with limestone;
- ✓ Excellent cost-benefit ratio, combining precision and durability at a low maintenance cost.
- ✓ **Fixed Rate:** Technology that maintains uniform distribution regardless of the tractor's speed.



Distribution system:
Stainless steel



Protection grid:
Agitator with smoother flow



Fixed Rate Version: Automatic distribution control

TECHNICAL SPECS

	DOUBLE DISC 1300/1600	DOUBLE DISC 1300/1600 FIXED RATE
⏻ Power source	Tractor PTO	Tracto PTO
📊 Capacity	1300/1600 litres	1300/ 1600 litres
↕ Height	1292 /1386mm	1292 / 1386mm
↔ Width	2350mm	2350mm
↔ Working width (range)	16 up to 36 metres	16 up to 36 metres
🔄 Required rotation at PTO	540 RPM	540 RPM
⚡ Required power at PTO	30 hp	30 hp
📦 Approx. weight	274 kg/279 kg	274 kg/ 279 kg
🖨 Fixed Rate System	No	Yes