



JF HELIX DUO 1300 1600 S2

Spreaders

Discover the innovative JF HELIX DUO 1300/1600 S2, the solution you have been looking for to cover your land with productivity! With its new modern and resistant design, it is the ideal equipment to help you save and spread fertilizers and seeds with precision. Its system allows the fertilizer or seed to reach the spreading disc without suffering impacts and to be launched smoothly and precisely, avoiding fragmentation.



BENEFITS

- ✓ The Helix Duo precision system with a central chamber technology allows for a smooth, bump-free launch with less dust and minimal wind influence, saving fertilizers and seeds;
- ✓ The discs, vanes, gates, and bottom closure are made of stainless steel;
- ✓ The adjustable vanes have a simple adjustment pin, and no tools are required;
- ✓ The polyethylene hopper is resistant to oxidation and has UV protection, with easy maintenance and cleaning;
- ✓ Work can be done on the edges, where the fertilizer can be spread on one side only;
- ✓ Hydraulic system for opening and closing the right and left gates (independent or simultaneous), ensuring precise application.



The Helix Duo precision system with a central chamber allows for smoother flow, leading to distribution with less dust and saving fertilizers/seeds.



Distribution system: Stainless steel




Eccentric agitator for better distribution flow



Protection grid: Agitator with smoother flow

CALIBRATION KIT INCLUDED



TECHNICAL SPECIFICATIONS

⏻ Power source	Tractor PTO	↔ Working width (range)	9 up to 24 meters
📊 Capacity	1300/1600 liters	↻ Required rotation at PTO	540 RPM
↑↓ Height	1292/1386mm	⚡ Required power at PTO	30 hp
↔ Width	2350mm	📦 Approx. weight	304 kg/309 kg